

What is claimed is:

1. A stage device comprising:

a stage controllable in at least one degree of freedom;

a supporting stage; and

at least one pair of electromagnetic actuator devices that couple said stage to said supporting stage for control in at least one of said degrees of freedom, each electromagnetic actuator device comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion, the actuating portion or the relative moving portion of said pair of electromagnetic actuator devices being mounted adjacent a single side of said stage in association with a direction of force produced by said pair of electromagnetic actuator devices.

2. The stage device of claim 1, wherein said actuating portion of said electromagnetic actuator device is mounted on said supporting stage, and said relative moving portion of said electromagnetic actuator device is mounted to said stage adjacent to said actuating portion within a predetermined gap defined by said electromagnetic actuator device.

3. The stage device of claim 1, wherein one relative moving portion is used as both of said relative moving portions of said pair of electromagnetic actuator devices.

4. The stage device of claim 2, wherein both of said actuating portions of said pair of electromagnetic actuator devices are mounted on said supporting stage, and a pair of corresponding relative moving portions are mounted on said stage adjacent one another and within a predetermined gap defined by said electromagnetic actuator devices.

5. The stage device of claim 4, wherein said pair of corresponding relative moving portions are peripherally mounted on said stage.

5 6. The stage device of claim 5, further comprising at least one mount member that extends from said stage, wherein said pair of corresponding relative moving portions are mounted on said mount member such that a resultant force from actuation of said pair of electromagnetic actuator devices is transferred to said stage through said mount member.

10 7. The stage device of claim 1, wherein said stage is positionally controllable in at least three degrees of freedom, said at least one pair of electromagnetic actuator devices comprising at least three pairs of electromagnetic actuator devices.

15 8. The stage device of claim 7, wherein two of said at least three pairs of electromagnetic actuator devices are aligned substantially parallel to a first direction, and a third of said at least three pairs of electromagnetic actuator devices is aligned in a second direction substantially perpendicular to said first direction.

20 9. The stage of claim 8, wherein said first and said second directions are within a plane in which a main surface of said stage substantially lies.

 10. The stage device of claim 8, wherein said first direction is substantially parallel to a moving direction of said supporting stage.

25 11. The stage device of claim 1, wherein said electromagnetic actuator device comprises a variable reluctance actuator.

12. The stage device of claim 1, wherein said at least one pair of electromagnetic actuator devices comprises three pairs of electromagnetic actuator devices that interconnect said stage and said supporting stage and are actuable to control said stage in three degrees of freedom.

5

13. The stage device of claim 12, further comprising at least one additional electromagnetic actuator device mounted between said stage and said supporting stage and actuable to control said stage in at least one additional degree of freedom.

10

14. The stage device of claim 13, further comprising at least one supplemental vertical support mounted between said stage and said supporting stage, and disposed at the substantially same location relative to the stage as said additional electromagnetic actuator device.

15

15. The stage device of claim 13, further comprising:

a plurality of supplemental vertical supports, for each of said additional electromagnetic actuator devices, mounted between said stage and said supporting stage, and disposed at the substantially same location relative to the stage as said additional electromagnetic actuator device; and

20

a suspending member that is supported by said plurality of supplemental vertical supports and flexibly supports the stage.

25

16. The stage device of claim 15, wherein said additional electromagnetic actuator device comprises at least one additional pair of electromagnetic actuator devices disposed adjacent each other, each electromagnetic actuator device comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion in a vertical direction, and one of said actuating portion and

said relative moving portion is mounted on said stage and the other of said actuating portion and said relative moving portion is mounted on said supporting stage.

5 17. The stage device of claim 16, further comprising a flexible member that connects the suspending member and at least one of the relative moving portions of said additional pair of electromagnetic actuator devices.

10 18. The method of claim 17, wherein the flexible member connects the suspending member and the at least one of the relative moving portions of said additional pair of electromagnetic actuator devices through a hole formed vertically within the actuating portion positioned above said at least one of the relative moving portions of said additional pair of electromagnetic actuator devices.

15 19. The stage device of claim 16, wherein one relative moving portion of said additional pair of electromagnetic actuator devices is used as both of said relative moving portions of said additional pair of electromagnetic actuator devices, said two actuating portions of said additional pair of electromagnetic actuator devices are vertically aligned with said one relative moving portion interposed between the two actuating portions.

20 20. The stage device of claim 12, wherein said electromagnetic actuator device comprises a variable reluctance actuator.

25 21. The stage device of claim 13, wherein said electromagnetic actuator devices and said additional electromagnetic actuator device comprise a variable reluctance actuator.

22. The stage device of claim 13, wherein said additional electromagnetic actuator device comprises a voice coil motor.

5 23. The stage device of claim 13, wherein said at least one additional electromagnetic actuator device comprises three additional electromagnetic actuator devices mounted between said stage and said supporting stage and actuatable to control said stage in three degrees of freedom.

10 24. The stage device of claim 14, wherein said at least one additional electromagnetic actuator device comprises three additional electromagnetic actuator devices mounted between said stage and said supporting stage and actuatable to control said stage in three degrees of freedom, and said at least one supplemental vertical support comprises three supplemental vertical supports, each of said three supplemental vertical supports being disposed at the substantially same location as a corresponding electromagnetic actuator device of said three additional electromagnetic actuator devices.

15

20 25. The stage of claim 15, wherein said at least one additional electromagnetic actuator device comprises three additional electromagnetic actuator devices mounted between said stage and said supporting stage and actuatable to control said stage in three degrees of freedom, said plurality of supplemental vertical supports being provided for each of said three additional electromagnetic actuator devices and being disposed at the substantially same location as a corresponding electromagnetic actuator device of said three additional electromagnetic actuator devices.

25

26. The stage device of claim 22, wherein said pairs of electromagnetic actuator devices comprise variable reluctance actuators and said stage further

comprises supplemental vertical supports mounted between said stage and said supporting stage.

5 27. The stage device of claim 14 or 26, wherein at least one of said supplemental vertical supports comprises air bellows.

28. The stage device of claim 1, further comprising at least one non-contact vertical support member that levitates said stage above said supporting stage.

10 29. The stage device of claim 28, further comprising at least one supplemental vertical support mounted between said stage and said supporting stage, and disposed at the substantially same location relative to the stage as said non-contact vertical support member.

15 30. The stage device of claim 28, wherein said at least one non-contact vertical support member comprises three non-contact vertical support members that controls the position of said stage in three vertical degrees of freedom.

20 31. The stage device of claim 29, wherein said at least one non-contact vertical support member comprises three non-contact vertical support members that controls the position of said stage in three vertical degrees of freedom, and said at least one supplemental vertical support comprises three supplemental vertical supports, each of said three supplemental vertical supports being disposed at the substantially same location as a corresponding non-contact vertical support member of said three non-contact vertical support member.

25

32. The stage of claim 28, wherein each said non-contact vertical support member comprises an electromagnetic actuator device.

33. The stage device of claim 29, wherein each said non-contact vertical support member comprises an electromagnetic actuator device, and each said supplemental vertical support comprises air bellows.

5

34. The stage device of claim 30, wherein each said non-contact vertical support member comprises a voice coil motor having a magnet portion and a coil portion, one of said magnet portion and said coil portion being mounted on said stage and the other of said magnet portion and said coil portion being mounted on said supporting stage.

10

35. The stage device of claim 31, wherein each said non-contact vertical support member comprises a pair of electromagnetic actuator devices disposed adjacent each other, each electromagnetic actuator device comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion in a vertical direction, and one of said actuating portion and said relative moving portion is mounted on said stage and the other of said actuating portion and said relative moving portion is mounted on said supporting stage.

15

20

36. The stage device of claim 28, further comprising at least one dead weight support for vertically supporting a dead weight of said stage.

25

37. The stage device of claim 28, further comprising at least one bellows that couples said stage and said supporting stage and vertically supports a dead weight of said stage.

38. The stage device of claim 37, wherein said at least one bellows comprises three bellows.

39. The stage device of claim 1, further comprising:

a driving device that moves said supporting stage, and comprises a first portion connected to said supporting stage and a second portion that is movable relative to said first portion;
a base member that guides supporting stage in at least one direction; and
a supporting member that supports said second portion of said driving device.

40. The stage device of claim 39, wherein said driving device moves said supporting stage in a first direction and a second direction substantially perpendicular to said first direction.

41. The stage device of claim 39, wherein the force acting on said supporting stage is connected directly to ground through said supporting member without coupling with said base member.

42. The stage device of claim 39, wherein said base is isolated from a route of a reaction force generated by actuation of said driving device.

43. The stage device of claim 39, further comprising at least one position detection device that detects a position of said stage, said position detection device being connected to a member that is not coupled with said supporting member.

44. A lithography system comprising:
an illumination system that irradiates radiant energy; and
the stage device according to any of claims 1 to 43, said stage device carrying an object disposed on a path of said radiant energy.

45. The lithography system of claim 44, further comprising an optical system and said supporting stage substantially aligned with said optical system.

5 46. The lithography system of claim 44, further comprising a mask stage that holds a mask having a pattern, and said mask is positioned between said illumination system and said stage

10 47. The lithography system of claim 45, further comprising a frame that supports at least one of said illumination system and said optical system, and is dynamically isolated from said stage device.

48. The lithography system of claim 46, wherein said optical system is positioned between said mask and said stage.

15 49. A device on which an image has been formed by the lithography system of claim 44.

20 50. A method of making a stage device comprising:
providing a stage that is controllable in at least one degree of freedom;
providing a supporting stage; and
providing at least one pair of electromagnetic actuator devices coupling said stage to said supporting stage for control in at least one of said degrees of freedom, wherein each electromagnetic actuator device comprises an actuating portion and a relative moving portion that is movable relative to said actuating portion, both
25 actuating portions or both relative moving portions of said pair of said electromagnetic actuator devices being mounted adjacent a single side of said stage in association with a direction of force produced by said pair of electromagnetic actuator devices.

51. A method of making a lithography system comprising:
providing an illumination system that irradiates radiant energy; and
providing a stage device made by the method of claim 50.

5

52. A method of making a device utilizing the lithography system made by
the method of claim 51.

53. A method of positioning a stage comprising inputting opposing forces for
moving the stage in opposite directions at the substantially same location on the
stage, such that a pulling force for moving the stage in a first direction is inputted at
the same side of the stage as a pushing force for moving the stage in a second
direction opposite to the first direction.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
218

58. The method of claim 56, wherein said vertical actuator comprises at least one voice coil motor.

5 59. The method of claim 53, further comprising floating said stage with respect to a support stage such that positioning movements of the stage are performed with no physical contact occurring between the stage and the support stage.

10 60. The method of claim 59, wherein said floating comprises electromagnetically biasing the stage with respect to the support stage.

15 61. The method of claim 55, further comprising supporting a weight of the stage by a supplemental vertical force at the substantially same location as said vertical actuator.

20 62. The method of claim 61, wherein the supplemental vertical force is generated by air bellows, and the vertical actuator is a pair of electromagnetic actuator devices disposed adjacent each other, each electromagnetic actuator device comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion in a vertical direction.

63. The method of claim 53, wherein said pulling force is greater than said pushing force, resulting in a net force in said first direction.

25 64. The method of claim 53, wherein said pushing force is greater than said pulling force, resulting in a net force in said second direction.

65. An exposure method for forming a pattern on an object utilizing an optical system, the method comprising:

mounting said object on a stage;

moving a supporting stage substantially aligned with said optical system; and

5 moving said stage relative to said supporting stage by at least one pair of electromagnetic actuator devices coupling said stage to said supporting stage for control in at least one degree of freedom, both actuating portions of said pair of said electromagnetic actuator devices being mounted adjacent a single side of said stage.

10 66. The method of claim 65, wherein said actuating portion of said electromagnetic actuator device is mounted on said supporting stage, and a relative moving portion of said electromagnetic actuator device is mounted on said stage adjacent to said actuating portion within a predetermined gap defined by said electromagnetic actuator device.

15 67. The method of claim 65, wherein said stage is positionally controllable in at least three degrees of freedom, and said at least one pair of electromagnetic actuator devices comprises at least three pairs of electromagnetic actuator devices.

20 68. The method of claim 65, wherein said electromagnetic actuator device comprises a variable reluctance actuator.

25 69. The method of claim 65, wherein said at least one pair of electromagnetic actuator devices comprises three pairs of electromagnetic actuator devices that interconnect said stage and said supporting stage and are actuable to control said stage in three degrees of freedom.

70. The method of claim 65, further comprising levitating said stage above said supporting stage with at least one non-contact vertical support member.

5 71. The method of claim 70, further comprising supporting a weight of the stage by a supplemental vertical force at the substantially same location as said non-contact vertical support member.

72. The method of claim 65, further comprising:
moving said supporting stage with a drive device, said drive device comprises
10 a first portion connected to said supporting stage and a second portion that is movable relative to said first portion, said second portion being supported by a supporting member; and
guiding said supporting stage in at least one direction with a base member.

15 73. A method for making a device utilizing the exposure method of any of claims 65 to 72.

74. A stage device comprising:
a stage that has a holding portion where an object can be held, said stage
20 being controllable in at least one degree of freedom;
a first electromagnetic actuator device connected with said stage, said first electromagnetic actuator device moves said stage in one direction; and
a second electromagnetic actuator device connected with said stage, said
25 second electromagnetic actuator device moves said stage in an opposite direction of said one direction,

wherein said holding portion of said stage is not disposed between a first transferring portion where a first force from an actuation of said first electromagnetic actuator device is transferred to said stage and a second transferring portion where a

second force from an actuation of said second electromagnetic actuator device is transferred to said stage.

5 75. The stage device of claim 74, wherein said first and second electromagnetic actuator device comprise variable reluctance actuators.

76. The stage device of claim 74, further comprising a stage support, and said first and second electromagnetic actuator devices couple said stage to said stage support.

10 77. The stage device of claim 76, wherein said first and second electromagnetic actuator device each comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion, and one of said actuating portion and said relative moving portion is mounted on said stage and the other of said actuating portion and said relative moving portion is mounted on said stage support.

15 78. An exposure apparatus comprising:
an illumination system that irradiates radiant energy; and
20 the stage device according to any of claims 74 to 77.

79. A device on which an image has been formed by the exposure apparatus of claim 78.

25 80. A method of making a stage device comprising:
providing a stage that has a holding portion where an object can be held, said stage being controllable in at least one degree of freedom;

providing a first electromagnetic actuator device connected with said stage,
said first electromagnetic actuator device moves said stage in one direction; and

providing a second electromagnetic actuator device connected with said stage,
said second electromagnetic actuator device moves said stage in an opposite direction
of said one direction,

wherein said holding portion of said stage is not disposed between a first
transferring portion where a first force from an actuation of said first electromagnetic
actuator device is transferred to said stage and a second transferring portion where a
second force from an actuation of said second electromagnetic actuator device is
transferred to said stage.

81. A method of making an exposure apparatus comprising:

providing an illumination system that irradiates radiant energy; and
providing a stage device made by the method of claim 80.

82. A method of making a device utilizing the exposure apparatus made by
method of claim 81.

83. A method for driving a stage that has a holding portion where an object
can be held, said stage being controllable in at least one degree of freedom,
comprising:

moving said stage in one direction by transferring a first force from an
actuation of a first electromagnetic actuator device; and

moving said stage in an opposite direction of said one direction by
transferring a second force from an actuation of second electromagnetic actuator
device,

wherein said holding portion of said stage is not disposed between a first transferring portion where said first force is transferred to said stage and a second transferring portion where said second force is transferred to said stage.

5 84. An exposure method for forming a pattern on an object utilizing the method for driving a stage of claim 83.

85. An method for making a device utilizing the exposure method of claim 84.

10 86. A stage device comprising:
a stage controllable in a vertical direction;
a supporting stage;
at least one electromagnetic actuator device mounted between said stage and
15 said supporting stage for control in the vertical direction; and
at least one supplemental vertical support mounted between said stage and
said supporting stage, and disposed at the substantially same location relative to the stage as said electromagnetic actuator device.

20 87. The stage device of claim 86, wherein said at least one electromagnetic actuator device comprises at least one pair of electromagnetic actuator devices disposed adjacent each other, each electromagnetic actuator device comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion in the vertical direction, and one of said actuating portion and said
25 relative moving portion is mounted on said stage and the other of said actuating portion and said relative moving portion is mounted on said supporting stage.

88. The stage device of claim 87, wherein both of said actuating portions of said pair of electromagnetic actuator devices are mounted on said supporting stage, and both of said relative moving portions are mounted on said stage and within a predetermined gap defined by said electromagnetic actuator devices.

5

89. The stage device of claim 87, wherein one relative moving portion is used as both of said relative moving portions of said pair of electromagnetic actuator devices.

90. The stage device of claim 87, wherein said electromagnetic actuator device comprises a variable reluctance actuator.

91. The stage device of claim 86, wherein at least one of said supplemental vertical supports comprises air bellows.

92. The stage device of claim 86, wherein said stage is positionally controllable in three vertical degrees of freedom, said at least one electromagnetic actuator device comprising at least three electromagnetic actuator devices and said at least one supplemental vertical support comprising at least three supplemental vertical supports, each of said at least three supplemental vertical supports being disposed at the substantially same location relative to the stage as a corresponding electromagnetic actuator device of said at least three electromagnetic actuator devices.

93. A stage device comprising:
a stage controllable in a vertical direction;
a supporting stage;

at least one electromagnetic actuator device mounted between said stage and said supporting stage for control in the vertical direction;

5 a plurality of supplemental vertical supports, for each of said electromagnetic actuator devices, mounted between said stage and said supporting stage, and disposed at the substantially same location relative to the stage as said each of the electromagnetic devices; and

a suspending member that is supported by said plurality of supplemental vertical supports and flexibly suspends the stage.

10 94. The stage device of claim 93, wherein said at least one electromagnetic actuator device comprises at least one pair of electromagnetic actuator devices disposed adjacent each other, each electromagnetic actuator device comprising an actuating portion and a relative moving portion that is movable relative to said actuating portion in the vertical direction, and both of said actuating portions of said pair of electromagnetic actuator devices are mounted on said supporting stage, and
15 both of said relative moving portions are mounted on said stage and within a predetermined gap defined by said electromagnetic actuator devices.

20 95. The stage device of claim 94, further comprises a flexible member that connects the suspending member and at least one of the relative moving portions of said pair of electromagnetic actuator devices.

25 96. The stage device of claim 95, wherein the flexible member connects the suspending member and the at least one of the relative moving portions of said pair of electromagnetic actuator devices through a hole formed vertically within the actuating portion positioned above said at least one of the relative moving portions.

97. The stage device of claim 95, wherein the flexible member is a wire or a thin flexible rod.

5 98. The stage device of claim 95, wherein one relative moving portion is used as both of said relative moving portions of said pair of electromagnetic actuator devices, said two actuating portions are vertically aligned with said one relative moving portion interposed between the two actuating portions.

10 99. The stage device of claim 93, wherein said electromagnetic actuator device comprises a variable reluctance actuator.

100. The stage device of claim 93, wherein at least one of said supplemental vertical supports comprises air bellows.

15 101. The stage device of claim 93, wherein said stage is positionally controllable in three vertical degrees of freedom, said at least one electromagnetic actuator device comprising at least three electromagnetic actuator devices, said plurality of supplemental vertical supports being provided for each of said at least three electromagnetic actuator devices and being disposed at the substantially same location relative to the stage as a corresponding electromagnetic actuator device of
20 said at least three electromagnetic actuator devices.

25 102. A method of positioning a stage comprising:
floating the stage for control in a vertical direction with no physical contact to the stage using an electromagnetic force generated at a location underneath the stage;
and

supporting a weight of the stage by a supplemental vertical force at the substantially same location as the electromagnetic force.

5 103. The method of positioning a stage of claim 102, wherein the electromagnetic force is a sum of two forces in opposite directions generated by a pair of electromagnetic actuator devices disposed adjacent each other at the location underneath the stage.

104. The method of positioning a stage of claim 102, wherein the electromagnetic force is generated by a variable reluctance actuator.

10 105. The method of positioning a stage of claim 102, wherein the supplemental vertical force is generated by air bellows.

15 106. The method of positioning a stage of claim 102, further comprising controlling movements of the stage in three vertical degrees of freedom, by applying at least three electromagnetic forces at at least three locations underneath the stage and corresponding supplemental vertical forces for each of the electromagnetic forces.

20 107. A method of positioning a stage comprising:
floating the stage for control in a vertical direction with no physical contact to the stage using an electromagnetic force generated at a location underneath the stage;
supporting a suspending member using a supplemental vertical force generated at the substantially same location as the electromagnetic force; and
suspending the stage flexibly from the suspending member.

25 108. The method of positioning a stage of claim 107, wherein the electromagnetic force is a sum of two forces in opposite directions generated by a

pair of electromagnetic actuator devices disposed adjacent each other at the location underneath the stage

5 109. The method of positioning a stage of claim 108, further comprising suspending the stage using a flexible member that connects the suspending member and a relative moving portion of the electromagnetic actuator device mounted on the stage, said flexible member extending through a hole formed vertically within an actuating portion of the electromagnetic actuator device positioned above the relative moving portion.

10 110. The method of positioning a stage of claim 109, wherein the flexible member is a wire or a thin flexible rod.

15 111. The method of positioning a stage of claim 107, wherein the electromagnetic force is generated by a variable reluctance actuator.

20 112. The method of positioning a stage of claim 107, wherein the supplemental vertical force is generated by air bellows.

25 113. The method of positioning a stage of claim 107, further comprising controlling movements of the stage in three vertical degrees of freedom, by applying at least three electromagnetic forces at at least three locations underneath the stage and by suspending the stage from corresponding suspending members for each of the electromagnetic forces.

114. An exposure apparatus comprising:
an illumination system that irradiates radiant energy; and
the stage device according to any of claims 86 to 101.

115. An exposure method for forming a pattern on an object utilizing the method of positioning a stage according to any claims 102 to 113.

5

116. A stage device comprising:

a stage controllable in a vertical direction;

an electromagnetic target rigidly connected to the stage;

an electromagnet electromagnetically coupling with the stage for control in the vertical direction without physical contact to the electromagnetic target; and

10

a supplemental vertical support for supporting a weight of the stage,

wherein a force generated by the supplemental vertical support acts on the electromagnetic target for supporting the weight of the stage.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100